5 MP IP Bullet Camera



Features

- Sony Stavis(Extreme low light)
- 5MP(2592x1944)
- EXIR 120ft
- True Day / Night
- 3D DNR, DWDR,BLC
- IP66 Rating

MODEL	EDGE-5W
Camera	
Image Sensor	1/2.7" Sony Starvis CMOS
Minimum Illumination	0.05 lux @F1.2, AGC ON, 0 lux with IR
IR LED	EXIR 120ft Range
Shutter Time	1/25s ~ 1/100,000s
Lens	3.6mm Lens
Lens Mount	M12
Optical Filter	Mechanically Switching IR Filter
Noise Reduction	3D DNR
WDR	DWDR
Video Compression	H.265(+)/H.264
Bit Rate	32 Kbps~8Mbps
Image	
Max Resolution	5MP(2592x1944)
Frame Rate	20fps@5MP(2592x1944), 25fps@4MP(2592x1520)
Image Settings	Rotate Mode, Saturation, Brightness, Contrast, Sharpness adjustable
AGC/BLC	Yes
Network	
Plug and Play	Plug and Play with Nuvis NVRs
Protocols	HTTP/RTSP/FTP/NFS/SMTP/DHCP/NTP
Compatibility	ONVIF 2.6 , RTSP compatible
General Functionalities	dual stream, mirror, password protection, privacy mask
Network Interface	1 RJ45, 10/100M Ethernet port
General	
Power Supply	12 V DC ± 10%; PoE (802.3af)
Power Consumption	Max. 5W (8W with IR on)
Operating Temperature	-10°C ~ 60°C (14°F ~ 140°F) humidity 95% or less (non-condensing)
Dimensions	6.5”(W) x 3.5”(H) x 2.4”(D)
Bracket	3 Axis , Cable through
Weight	1.0lb
Weather Proof	IP66