x33 4MP IR IP PTZ Dome Camera

NDAA COMPLIANT



Features

- 4MP Full HD resolution
- 33x optical zoom
- 150m(492ft) IR distance
- True Day/Night, DNR, DWDR
- Support PoE+, AC24V,DC24V

MODEL	IPC6624SR-X33-VF
Camera	
Image Sensor	1/ 2.8" 4.0 MP Progressive Scan CMOS
Max Resolution	4MP(2688x1520) @ 15fps
Min. Illumination	0.003Lux @ Color(F1.5, AGC ON) 0Lux with IR
White Balance	Auto/ATW/Manual
AGC	Auto/Manual
S/N Ratio	>56dB
Optical Filter	Mechanically Switching IR Filter
WDR	120DB
DNR	Yes
Shutter Speed	1~1/100,000s
Focus Mode	Auto
Lens	
Focal Length	4.5~148.5mm, 33x
Aperture Range	F1.5~F4.0
Angle of View	51.4°~2.5° (H), 30.3° ~1.4° (V)
Pan & Tilt	
Pan / Tilt Range	Pan 360° endless; Tilt -15°~90° (Auto Flip)
Pan / Tilt Speed	Pan Speed 0.1° ~300° /s Tilt Speed 0.1° ~240° /s
Auto Scan	AB Scan, 360 Scan
Tour	16 Group (Max64 Preset)
Park Action, Power on Action	Memory/Home/Tour 1-3/360 scan/ AB scan//None
Auto Flip	Yes
Number of Preset	1024
IR LED	
IR Distance	Up to 150m(492 ft), 850nm
Interface	
Audio	1 Input /1Output
Alarm	2 Input / 1 Output
RS 485	RS-485(Pelco D/P)
Video Output	1 BNC
Local Storage	Micro SD, up to 256GB
Reset Button	Support
Network	
Ethernet	10Base-T/100Base-TX, RJ45 connector
Image Compression	Ultra 265, H.265, H.264, MJPEG
General	
Operating Temp.	-40°F~ 158°F(-40℃~ 70℃), ≤95% RH
Protection Level	IP66 standard 64KV Surge protection
Dimension	Φ89” dome ×15” height
Weight	12 lbs
Power Consumption	PoE+, AC24V, DC24V, Max 25W