4 Mega Pixel HD IP EXIR Bullet Camera



Features

- 4 megapixel H.265
- 30fps @ 4MP
- 120dB WDR
- 3D DNR, BLC,ROI
- IP67 Rating
- 2 EXIR(150ft)
- True Day / Night
- Junction Box available

MODEL	NUVIS 45WL
Camera	
Image Sensor	1/3" Progressive Scan CMOS
Minimum Illumination	0.018 lux @F1.6, AGC ON, 0 lux with IR
IRs	2EXIR (150ft)
Shutter Time	1/30s ~ 1/100,000s
Lens	4mm (F1.6) Hor:83°, Ver 45°, Diag : 99°
Lens Mount	M12
Optical Filter	Mechanically Switching IR Filter
Noise Reduction	3D DNR
WDR	120dB WDR
Camera Features	
Video Compression	H.265(+), H.264(+), Main Profile
H.265 Profile	Main Profile
Bit Rate	32 Kbps~16Mbps
Image	
Max Resolution	2688x1520
Frame Rate	30fps@ 4,2,1 MP
Image Settings	Saturation, brightness, contrast adjustable
BLC	Yes, zone configurable
Network	
Network Storage	NAS
Alarm Trigger	Line Crossing, Intrusion Detection, Face Detection, Motion detection, tampering alarm, network disconnect, IP address conflict, storage exception
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, UPnP, ICMP,IGMP,SNMP, FTP, 802.1X, QoS, HTTPS
Compatibility	ONVIF(Profile S&G), PSIA, CGI
General Functionalities (Security)	dual stream, heartbeat, mirror, password pr otection, privacy mask, watermark, IP addre ss filtering, Anonymous access
Network Interface	1 RJ45, 10 M/100 M Ethernet port
General	
Power Supply	12 V DC ± 10%; PoE (802.3af)
Power Consumption	Max. 8W with IR on
Operating Temperature	-30°C ~ 60°C (-22°F ~ 140°F) humidity 95% or less (non-condensing)
EXIR Range	Up to 150ft
Dimensions	Φ 3.8 Inch × 12Inch
Weight	2 lb
Weather Proof	IP67