2 MP IP PIR camera with Mic



Features

- 30fps @ 2MP(1920x1080)
- 3.7mm Pinhole lens
- 12 IR LEDs(50ft)
- Built-in Microphone
- True Day / Night
- 3D DNR, DWDR,BLC

MODEL	Neo-2PIR
Camera	
Image Sensor	1/2.9" Sony Progressive Scan CMOS
Minimum Illumination	0.01 lux @F1.2, AGC ON, 0 lux with IR
IR LED	12 IR LEDs (50ft)
Shutter Time	1/25s ~ 1/100,000s
Lens	3.7mm Pinhole lens
Lens Mount	M12
Optical Filter	Mechanically Switching IR Filter
Noise Reduction	2D/3D DNR
WDR	DWDR
Video Compression	H.264
Audio	Built-in Microphone
Bit Rate	32 Kbps~6Mbps
Image	
Max Resolution	2MP(1920x1080)
Frame Rate	30fps@2MP(1920x1080)
Image Settings	Saturation, brightness, contrast adjustable
AGC/BLC	Yes
Network	
Plug and Play	Plug and Play with Nuvis NVRs
Protocols	HTTP/RTSP/FTP/NFS/SMTP/DHCP/NTP
Compatibility	ONVIF 2.6 , RTSP compatible
General Functionalities	dual stream, mirror, password protection, privacy mask
Network Interface	1 RJ45, 10/100M Ethernet port
General	
Power Supply	12 V DC ± 10%; PoE (802.3af)
Power Consumption	Max. 5W (8W with IR on)
Operating Temperature	-20°C ~ 60°C (-4°F ~ 140°F) humidity 95% or less (non-condensing)
Dimensions	4.7"×2.8"×1.6"
Weight	1.0lb
Weather Proof	IP66
NVR	
NVR	NUVIS, PRIME, MEGA