x20 5MP IR IP PTZ POE Camera



Features

•5MP HD resolution
•20x optical zoom
•200ft Array IRs
•True Day/Night, DNR, DWDR
•DC12V/POE+

i

MODEL	Neo-520XQB
Camera	
Image Sensor	1/3" Sony CMOS
Resolution	5MP(2560x1920)@20fps, 4,3,2,1MP
Min. Illumination	0.02Lux@F1.6; 0Lux with IR
White Balance	Auto/ATW/Manual
AGC	Auto/Manual
S/N Ratio	>50dB
Optical Filter	Mechanically Switching IR Filter
Backlight Compensation	BLC/DWDR
DNR	Yes
Shutter Speed	1/2~1/20,000s
Focus Mode	Auto
Lens	
Focal Length	f=4.7(Wide) ~94(Tele)mm
Field of view	Diagonal 65°~4°(T)
PTZ	
Pan/Tilt Range	Pan 360°Endless，Tilt: 0~93°
Manual Speed	Pan: 0.1°-45°/s Tilt: 0.1°-30°/s
Auto Scan	AB Scan, Pan Scan
Tour	8 Group (Max16 Preset)
Park Action, Power on Action	Home/Tour 1-3/360 scan/AB scan
Communication	TCP/IP, RS-485(Pelco D/P)
Number of Preset	220
IR LED	
IR Distance	6 Array IRs(1.7inch)+ 250ft
Network	
Ethernet	10Base-T/100Base-TX, RJ45 connector
Video compression	H.264/H.265/M-JPEG
General	
Operating Temp.	-40°F~ 158°F(-40℃~ 70℃)
Humidity	90% or less
Protection Level	IP66 standard TVS 6,000V lighting protection, surge protection and voltage transient protection
Dimension	Φ6” dome ×10” height
Weight	6 lbs
Power	DC12V,3A /POE+
NVR	
NVR	NUVIS