# 4K, 4ch Plug & Play PoE NVR



## Features

- 4ch IP camera Input
- 4 PoE  Port
- Up to 8 Megapixels Resolution Recording
- Up to 4 ch @1080P  synchronous playback
- HDMI output at up to  4K(3840*2160)
- 1 SATA HDD

## Rear Panel

1.Two Way Audio In
2. LAN Network Interface
3. Power Switch
4. Network Interfaces with PoE
5. Audio Out
6. VGA Output
7. HDMI Interface
8. USB Interface
9. DC48V Power Input
10. GND

| MODEL | NUVIS NVR7104P4 |
|---|---|
| **Video / Audio input** | |
| IP Video input | 4 ch, 4 PoE(af/at) |
| Two-way Audio | 1 ch, RCA |
| **Video/Audio output** | |
| Recording resolution | 8MP/6MP/5MP/4MP/3MP/1080p UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF |
| HDMI | 4K(3840*2160),1920 × 1080P,1600 × 1200 1280 × 1024, 1280 × 720 |
| VGA | Max. 1920x1080P, simulation of HDMI |
| Audio output | 1 ch, RCA (Linear, 1kΩ) |
| Playback resolution | 8MP/6MP/5MP/4MP/3MP/1080p UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF |
| Decode | 1ch@8MP, 4ch@1080P |
| **Hard disk** | |
| Type | 1 SATA interfaces(6TB Max Each) |
| **External Interface** | |
| Network interface | 1 x RJ-45 10/100/1000 Mbps 4 x10/100 Mbps PoE(af/at) |
| Input | 40 Mbps |
| Output | 80 Mbps |
| USB interface | USB 2.0 x1 @front, USB 3.0 x1 @rear |
| Alarm in/out | N/A |
| **General** | |
| Power Supply | DC48V, 1.36A |
| Power Consumption | Max. 65 W |
| Working Temperature | 14 °F ~ 131 °F |
| Working humidity | 10%~90% |
| Dimensions | 12.4"×9.4"×1.9“(315×240×48mm) |
| Weight | 2.2lb(1Kg) |
| **CMS/Web/Smart Phone** | |
| CMS | iVMS |
| Web | 4ch View/4ch Playback |
| Smart Phone Apps | Guarding Expert ( iphone, android) Guarding Expert HD(iPad) |
| DDNS | Free DDNS service |

