4K, 32ch NVR, 8HDD Bay



MODEL	Nuvis NVR9632-I8
IP Video input	32 ch
Two-way Audio	1-ch RCA(2.0Vp-p, 1kΩ)
Video/Audio output	
Recording resolution	12MP/8MP/6MP/5MP/4MP/3MP/1080p UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF
HDMI1/VGA1	Max.4K Res., 32ch View, simulation
HDMI2/VGA2	Max.1080P Res., 32ch View, simulation
Audio output	2-ch, RCA (2.0Vp-p, 1KΩ)
Live View/Playback resolution	12MP/8MP/6MP/5MP /3MP /1080P /UXGA /720P /VGA /4CIF /DCIF /2CIF /CIF /QCIF
Decode Capacity	4ch@8MP, 16ch@2MP
Hard disk	
SATA	Up to 8 SATA interfaces(12TB Max Each)
RAID	RAID0, RAID1, RAID5, RAID10
e-SATA	1 eSATA
External Interface	
Network interface	2ea x RJ-45 10 /100 /1000 Mbps
Input	320 Mbps
Output	256 Mbps
Serial interface	1 RS-232, 1 RS-485
USB interface	2 x USB 2.0 at front, 1 x USB3.0 at rear
Alarm Input	16ch
Alarm Output	4ch
General	
Power Supply	100~240VAC, 6.3A, 50~60Hz
Power Consumption	≤ 30 W (without hard disk or DVD-R/W)
Working Temperature	14 °F ~ 131 °F
Working humidity	10%~90%
Chassis	19-inch rack mounted 2U chassis
Dimensions	17.5 × 18.5 × 3.5″
Weight	22 lb
CMS/Web/Smart Phone	
CMS	iVMS
Web	16ch View/16ch Playback
Smart Phone Apps	Guarding Expert (iphone, android) Guarding Expert HD(iPad)
DDNS	Free DDNS service

Features

- 32ch IP camera Input
- 2 ea Gigabit Port
- Up to 12 Megapixels Resolution Recording
- Up to 16 ch @1080P synchronous playback
- HDMI output at up to 4K(3840*2160)
- HDMI1/VGA1, HDMI2,VGA2
- 8 SATA HDD, RAID

Rear Panel

1. LINE IN, RCA connector for audio input
2. RS-232 interface
3. Ground
4. Power switch
5. AC 100V ~ 240V
6. LAN1/LAN2 Interface
7. AUDIO OUT, RCA connector for audio output
8. HDMI1
9. VGA1
10. VGA2
11. HDMI2
12. USB 3.0 Interface
13. eSATA interface
14. Controller Port, Alarm In/Alarm Out

