
4ch TVI/CVI/AHD/CVBS/IP DVR 1U



Features

- H.265(+)/H.264(+) video compression
- HD TVI/HD CVI/AHD/CVBS/IP Hybrid
- 3MP TVI on ch1
- HDMI/VGA output at up to 1920×1080P
- Independent CVBS spot out



3. HDMI Interface
4. VGA Interface
5. AUDIO OUT, RCA Connector
6. LAN Network Interface
7. RS-485 Serial Interface
8. 12VDC Power Input
9. GND
10. CVBS(BNC) out
11. AUDIO IN, RCA Connector
12. Power Switch

MODEL	NUVIS TVK1104
Video / Audio input	
Video Compression	H.265(+)/H.264(+)
Video Input	4ch BNC (HD TVI/HD CVI/AHD/CVBS)
HD TVI Input	3 MP(ch1 only), 1080p30, 1080p25, 720p60, 720p50, 720p30, 720p25
HD CVI/AHD Input	1080p25, 1080p30, 720p25, 720p30
CVBS input	NTSC/PAL
IP Video input	1ch,4MP (Total 5ch)
Audio Input	1 ch, RCA
Two-way audio	1ch, RCA (using audio input)
Video/Audio output	
HDMI / VGA Output	HDMI & VGA: simulation (1920x1080)
CVBS	1ch BNC, 704x480 Resolution, Spot Out Monitor Only(No Menu)
Encoding resolution	3MP,1080P @15fps 720P,VGA/WD1/4CIF@30fps
Encoding resolution (Sub Stream)	WD1/4CIF@12fps, CIF@30fps
Video Bit Rate	32 Kbps ~ 6 Mbps
Stream Type	Video/Video&Audio
Audio Output	1-ch, RCA (Linear, 1KΩ)
Audio Bit Rate	64kbps
Synchro Playback	4ch
Dual Stream	Yes
Remote connections	128
Hard Disk	
Capacity	Up to 6TB capacity for each Disk
SATA	1 SATA interface
External Interface	
Network Interface	1 RJ45 10M/100M
USB Interface	2 USB2.0 Interface
Serial Interface	1 RS-485 interface
General	
Power Supply	12V DC
Consumption	<15W
Working Temperature	-10 ºC ~+55 ºC (14 ºF ~ 131 ºF)
Working Humidity	10%~90%
Chassis	1U chassis
Dimension	315 × 242 × 45mm (12.4 × 9.5 × 1.8 inch)
Weight	≤ 1.5Kg (3.3lb)
CMS/Web/Smart Phone	
CMS	iVMS
Web	Live View/Remote Play Back/Remote Setup
Smart Phone Apps	Guarding Expert (iphone, android) Guarding Expert HD(iPad)
DDNS	Free DDNS service