POEI-82G

8 Ports Gbit Industrial PoE Switch



Features
-8x PoE Ethernet Port 10/100/1000 Mbps
-2x Gigabit Fiber port
-Single port supports PoE power:30W
-Operating temperature -40℃~85℃
-Supports 6KV DC Ethernet ESD protection
-Din Rail

Downstream Ports	8 x 10/100/1000 Mbit (8 Ports PoE)
Uplink Ports	2 x 1000Mbit Fiber port
Network Standard	IEEE802.3, IEEE802.3i, IEEE802.3u, IEEE802.3ab, IEEE802.3x
Bandwidth	20Gbps
Packet Forwarding Rate	15Mpps
Forwarding Modes	Store and Forward
Packet Buffer	2Mbit
MAC Address Table	8K
PoE Standard	802.3af/at, max 30W/port
PoE Power Method	End-span
LED Indicator	PWR : RED Fiber : Link 2 (Green) Ethernet : Yellow
Power Input	48 to 57V DC redundant power
Power supply	Output:54V, 2.2A, 118.8W, Input: 110~240V
Surge protection	4KV
Operating Temperature	-40℃~85℃
Storage temperature	-40℃~85℃
Humidity(Non-condensin)	5%-90%
Enclosure	IP40 aluminum housing
Installation	DIN rail
Dimension（L×W×H）	144mm×103mm×45mm
Weight(Kg)	0.6 kg