HD1080P TVI(Turbo Video Interface)
Varifocal Indoor dome camera





Features

- Sony 1080 Image Sensor
- HD TVI(1080P), Analog Hybrid
- True Day/Night
- 2.8~12mm 2 MegaPixel Lens
- OSD(UTC, Button on the Cable)
- 2DNR, 3DNR
- Sens Up, DWDR

MODEL	TV212D
Camera	
Image Sensor	1/3'' Sony
Effective Pixels	1920(H)*1080(V)
Min. Illumination	0.05 Lux
Scanning System	Progressive Scan
Shutter Time	1/60 s to 1/60,000 s
Lens	2.8~12mm 2Mega Pixel Lens/F2.0
Angle of view	104~36°
Lens Mount	M12
Angle Adjustment	Pan: 0 - 360°, Tilt: 0 - 80°, Rotation: 0 - 300°
Day & Night Mode	External, Internal, Color, Mono
Sen Up	Auto, Max x30
Wide dynamic range	D-WDR
Synchronization	Internal synchronization
Video Frame Rate	30fps(NTSC) @ 1080p
Video Output	1x HD TVI (BNC), 1x Analog (BNC)
S/N Ratio	48dB (min) (ACG closed)
OSD menu	UTC, Button on the cable
Menu	
Noise Reduction	2DNR, 3DNR
Auto White Balance	AUTO
AE Mode	Normal/Front Light/Back Light
AGC	AUTO
GENERAL	
Dimension	¢ 5" x 4"(H)
Power Source	DC12V 250mA
3 Axis	3 Axis Mount
Hanger	Bottom of dome is attachable Hanger for easy install
Operation Temperature	-10℃ ~ +50℃ RH95% Max
Storage Temperature	-20℃ ~ +60℃ RH95% Max
Weight	1.0lb